Certificate No.: 2531-CPR-CSP11125





CERTIFICATE OF CONSTANCY OF PERFORMANCE

Issued by DBI Certification, notified body No. 2531.

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

45681-508 S65 conventional 12V relay base for use in fire detection and alarm systems

The product fulfils the essential characteristic:

See Annex 1

Intended use: Applications related to automatic fire alarm systems

Placed on the market under the name or trade mark of:

Apollo Fire Detectors Ltd. 36 Brookside Road Havant, Hampshire, GB-P09 1JR United Kingdom

and produced in the manufacturing plant:

Apollo Fire Detectors Ltd. 36 Brookside Road Havant, Hampshire, GB-P09 1JR United Kingdom

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standards

EN 54-18:2005 : Fire detection and fire alarm systems - Part 18: Input/output devices

under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

The attached annexes form part of this certificate.

Date of issue 2020-12-09.

This certificate will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly unless suspended or withdrawn by the notified product certification body.

(This certificate supersedes the previous version of this certificate issued 2019-10-28)

This certificate was first issued 2019-10-28.

Merete Poulsen Responsible for evaluation Thomas Anthony Wilson Responsible for certification decision



Certificate No.: 2531-CPR-CSP11125





Annex 1

EXTENT

Type:

45681-508 S65 conventional 12V relay base for use in fire detection and alarm systems

Performance

Essential characteristics	Clauses in EN 54-18:2005	Performance
Response delay (response time)	5.2 1)	Pass
Performance under fire conditions	5.1.4	Pass
Operational reliability	5.1.4	Pass
Durability of operational reliability; temperature resistance	5.3, 5.4	Pass
Durability of operational reliability; vibration resistance	5.8 to 5.11	Pass
Durability of operational reliability; humidity resistance	5.5, 5.6	Pass
Durability of operational reliability; corrosion resistance	5.7	Pass
Durability of operational reliability; electrical stability	5.2, 5.12	Pass

1) Response delays may not be a function of the input/output device, in which case no assessment is made as part of this standard



Certificate No.: 2531-CPR-CSP11125





Annex 2

TEST DOCUMENTATION

Accredited Laboratory	Report no.	Date
BRE	TE 245928	2009-09-15
BRE	TE-P117470-1000 Issue: 1	2020-11-20

TECHNICAL BASIS

	File Number			Title
45681-508		Build Standa	ard	

