Certificate No.: 2531-CPR-CSP11013



CERTIFICATE OF CONSTANCY OF PERFORMANCE

Issued by DBI Certification, notified body No. 2531.

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

55100-908 XP95 Analogue Addressable Manual Call Point with Short Circuit Isolator

The product fulfils the essential characteristic:

See Annex 1

Intended use: Applications related to automatic fire alarm systems

Placed on the market under the name or trade mark of:

Apollo Fire Detectors Ltd. 36 Brookside Road Havant, Hampshire, GB-P09 1JR United Kingdom

and produced in the manufacturing plant:

Honeywell Life Safety Romania SRL Str. Salcamilor 2bis Lugoj 305500 Romania

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standards

EN 54-17:2005/AC:2007 : Fire detection and fire alarm systems - Part 17: Short-circuit isolators
EN 54-11:2001/A1:2005 : Fire detection and fire alarm systems - Part 11: Manual call points

under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

The attached annexes form part of this certificate.

Date of issue: 2021-11-18.

This certificate will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly unless suspended or withdrawn by the notified product certification body.

(This certificate supersedes the previous version of this certificate issued 2019-10-24)

This certificate was first issued 2019-10-24.

Allan Laursen
Responsible for evaluation

Merete Poulsen
Responsible for certification decision

DANAK Prod. Reg. Nr. 7023

Certificate No.: 2531-CPR-CSP11013





Annex 1

EXTENT

Type

55100-908 XP95 Analogue Addressable Manuel Call Point with Short Circuit Isolator. Type A Indoor Use.

Variants:

55100-908LIM (branded as Limotec)

55100-908SIL XP95 Analogue Addressable Manual Call Point with Short Circuit Isolator

Ancillary:

Surface Mounting Box

Performance

Essential characteristics	Clauses in EN 54-11:2001	Performance
Nominal activation	4.3.2, 4.4, 4.7.1, 4.7.4, 5.2, 5.3	Pass
conditions/Sensitivity, Response		
delay (response time) and		
Performance under fire conditions		
Operational reliability	4.2, 4.3.1, 4.5, 4.6, 4.7.2, 4.7.3, 4.7.5,	Pass
	4.8, 5.4, 5.5	
Durability of operational reliability	5.7, 5.8*, 5.9	Pass
and response delay; temperature		
resistance		
Durability of operational reliability;	5.14 to 5.17	Pass
vibration resistance		
Durability of operational reliability;	5.10, 5.11*, 5.12	Pass
humidity resistance		
Durability of operational reliability;	5.11, 5.13	Pass
corrosion resistance		
Durability of operational reliability;	5.6, 5.18†	Pass
electrical stability		

^{5.8*} Outdoor Devices only

^{5.18&}lt;sup>†</sup> Devices with active electronic components only

Essential characteristics	Clauses in EN 54-17:2005	Performance
Performance under fire conditions	5.2 1)	Pass
Operational reliability	4	Pass
Durability of operational reliability; temperature resistance	5.4, 5.5	Pass
Durability of operational reliability; vibration resistance	5.9 to 5.12	Pass
Durability of operational reliability; humidity resistance	5.6, 5.7	Pass
Durability of operational reliability; corrosion resistance	5.8	Pass
Durability of operational reliability; electrical stability	5.3, 5.13	Pass

¹⁾ This is assuming that the effect of the fire is to cause a short circuit in the transmission path that is protected by these devices



^{5.11*} Outdoor Devices only

[–] extracts only with written permission from DBI Certification A/S.









Certificate No.: 2531-CPR-CSP11013





Annex 2

TEST DOCUMENTATION

Accredited Laboratory	Report no.	Date
BRE	TE 222766	2006-07-07
BRE	222766-SW	2006-08-07

TECHNICAL BASIS	
File Number	Title
55100-908	Build Standard



